



# *Industrial Fiberglass Specialties, Inc.*

521 Kiser Street

Dayton, Ohio 45404-1641

Telephone = (937) 222-9000 - Fax = (937) 222-9020

## **Series 5400 Filament Wound FRP Composite Phenol Novolac Epoxy Pipe and Fittings**

**For small diameter severe corrosive industrial service**

---

### **Uses and Applications:**

Chemical process piping  
Geothermal  
Acid Drains  
Corrosive and abrasive slurries  
Waste water and sewage systems  
Process plant piping  
Power plant & fly ash piping  
Food processing plant piping  
Plant piping  
Water treatment piping  
Brine and brackish water  
Piping systems for alkalies and non-oxidizing acids  
Industrial service for corrosive liquids

---

### **Description:**

Filament-wound fiberglass reinforced epoxy composite pipe.  
ASTM D-2996 Classification Type I, Grade 1, Class F.

### **Composition:**

Nominal 40 mil inner corrosion barrier/liner reinforced with Nexus synthetic veil, carbon veil, and/or C-Veil; followed by a fiberglass filament wound structural overwrap.

A premium grade amine-reacted heat-cured epoxy phenol novolac resin, pigmented black for UV inhibition, is used throughout all laminates.

Operating temperatures up to 350° F.

---

### **Pipe Sizes:**

173+ different diameters, ranging from a teeny 3/8" diameter up to a mammoth 84" diameter. Pipe available built to iron pipe outside diameters (ASTM D-2996, Table #3); as well as pipe built to chemical process piping inside diameter standards (ASTM D-2996, Table #4). A current list of pipe sizes is available upon request. New sizes are being added regularly.

### **Pipe Lengths:**

3/8" & 1/2" diameter pipe are built in 5 ft. lengths.

3/4" & 7/8" diameter pipe are built in 7 ft. lengths.

1" thru 1-1/2" diameter pipe is built in 10 ft. lengths.

2" thru 24" diameter pipe is available in 20 ft. lengths.

8" thru 84" diameter pipe is available in 40 ft. lengths.

---

**Performance:**

Good corrosion resistance over a wide temperature range. Temperatures from sub-zero to 350°F.

**Advantages:**

Working pressures from NBS-PS-15-69 duct to 450 psi+, depending upon size and wall thickness.

Vacuum to -14.7 psig for all sizes, by selection of wall thicknesses, ribs and filament wind angle.

Available for earth burial, all depths, with selection of wall thicknesses, ribs and filament wind angle.

Weighs 1/6 as much as steel. Thus, lower installed costs.

The resins used in Series 5400 pipe meet the requirements of F.D.A. regulations 21-CFR-175.105 and 21CFR 177.2420.

Smooth inner surface produces very low frictional loss for reduced pumping and fan blower costs. Hazen-Williams flow coefficient of 155.

Recommended for a wide range of corrosion applications. Consult with Industrial Fiberglass Specialties for specific project recommendations.

---

**Joining Systems:**

Bell (socket) and spigot structural adhesive weld bonded joints. Adhesive bonded joints are available as your choice of straight/straight, straight/taper and taper/taper.

Threaded joints (NPT) through 12" diameter Other thread configurations available upon special order.

Flanges, all sizes through 84" diameter Including the superior filament wound socket flanges for sizes through 1/2" diameter through 42" diameter ANSI 150 lb., 300 lb. and 600 lb. all available as standard. Any pressure rating and drilling pattern available on order.

Van Stone, loose ring style, flanges

Flange Spacers - all diameters, bolt hole patterns and thicknesses, built to order.

Bell and spigot O-Ring joints, thru 84" diameter

Bell and spigot O-Ring joints with locking key for restrained ends.

Mechanical Couplings, including Victaulic and Taylor-Kerr.

Expansion Joints, including triple O-Ring style for fly ash lines

Speed-Seal O-Ring true unions

Repair (maintenance) couplings.

---

**Physical Properties:**

See Table 1 for typical physical properties of Series 5400 filament wound FRP composite pipe and duct. These are conservative properties that can be used for the design of FRP pipe and duct for pressure, vacuum, supported span and burial conditions.

**Mechanical Properties:**

Contact Industrial Fiberglass for recommendations on the appropriate design formulas to be used for FRP composite pipe and duct.

---

**Burial Installations:**

As a custom manufacturer of pipe and fittings, we can design and build pipe to handle burial conditions ranging from live loads due to highway and rail traffic - to earth loads of 100 ft. or greater. We even have experience with underwater installations. Our engineers will welcome the opportunity to work with you on a pipe design, backfill selection and installation methods to meet your specific requirements. The result will be your lowest cost per year of service life (installed basis).

---

**Supported Span Installations:**

Again, we can design and build pipe to provide you the lowest cost for supported span installed pipe. Since we are not limited to just a few pipe wall thicknesses and filament winding angles - we can select and choose the combination of pipe design and support design and cost that will provide your "best buy". Consult with our engineers for help with your specific requirements.

---

**Fittings:**

Elbows, standard are 22-1/2°, 30°, 45°, and 90°. Any angle elbow available on special order. Elbows through 48" diameter are available as smooth radius. Mitered elbows are available in all sizes.

Reducing elbows

Tees

Reducing tees

Concentric taper body reducers

Eccentric taper body reducers

Saddles, with FRP and stainless steel threaded outlets, bell outlets, spigot outlets and flanged outlets.

Wear pads (blank saddles)

Crosses

Reducing Crosses

Laterals

Reducing Laterals

True wyes.

P-Traps and 180° U-Bends.

Floor drains

Expansion joints

Pipe couplings

Threaded (NPT) couplings

Adapters, bell by NPT thread (male or female threads available).

Adapters, spigot by NPT thread (male or female threads available).

Pipe nipples

Threaded nipples

Reducing bushings and threaded adapter bushings.

Fitting and pipe plugs. Pipe caps.

Blind flanges

Threaded flanges

Reducing flanges

Orifice flanges

All fittings are available as adhesive socket, plain end, flanged end, bell and spigot O-Ring; or any combination. See full Industrial Fiberglass' catalog for sizes, dimensions and tolerances. Fittings are available from 1/2" diameter through 84" diameter We welcome the opportunity to work with our customers on special fittings.

Table 1

***Industrial Fiberglass Specialties, Inc.***

521 Kiser Street - Dayton, Ohio 45404-1641  
Telephone = (937) 222-9000 - Fax = (937) 222-9020

**Properties of Series 5400 Filament Wound FRP Composite Pipe**

Corrosion Liner..... 40 mil Nexus and/or carbon veil reinforced  
Resin (Liner)..... Premium grade heat-cured phenol novolac epoxy  
Structural Wall..... Filament wound overwrap  
Resin (FW Overwrap)... Premium grade heat-cured phenol novolac epoxy

**Elastic and Strength Properties of Glass Filament Reinforced Wall**

**Hoop Tensile: (Based on loading of pipe hydrostatically)**

Ultimate (porosity)..... 20,000 psi  
Yield..... 12,800 psi  
Allowable..... 6,700 psi  
Modulus of Elasticity..... 3,600,000 psi

**Tensile: (Based on loading of pipe as a tension member)**

Ultimate (rupture)..... 12,200 psi  
Yield..... 5,000 psi  
Allowable..... 3,300 psi  
Modulus of Elasticity..... 1,800,000 psi

**Flexural: (Based on loading of pipe as a beam)**

Ultimate (rupture)..... 15,700 psi  
Yield..... 6,100 psi  
Allowable..... 4,000 psi  
Modulus of Elasticity..... 1,700,000 psi

**Torsion: (Based on loading of pipe as a shaft in torsion)**

Ultimate (rupture)..... 16,200 psi  
Allowable Shear..... 5,500 psi  
Shear Modulus..... 750,000 psi

**Compression: (Based on loading of pipe as a "short" column)**

Ultimate (rupture)..... 11,200 psi  
Yield..... 7,000 psi  
Allowable..... 3,700 psi  
Modulus of Elasticity..... 1,400,000 psi

**Thermal Properties:**

Coefficient of Thermal Expansion..... 0.0000085 in./in./deg. F  
Thermal Conductivity..... 2.3 BTU/hr./sq. ft./deg. F/in. thick.